MEPROLIGHT® SIGHTS

ML-10997

Front Night Sight for RUGER LCR Revolver

□ SET

□ F.S.


Installation Instructions

WARNING: This sight contains a small quantity (18 millicuries or less) of radioactive tritium in gaseous form. No attempt must be made to disassemble the sight. If a sight is defective, please contact the distributor shown on the reverse side of this page for instructions – or, if outside the US, please contact your local distributor.

WARNING: Before starting, make sure the weapon is unloaded.

NOTE: BEFORE CONTINUING, READ WARRANTY AND RECORD LOT NUMBER (1 or 2 letters, normally found on the side of the sight).

NOTE: The sketch below is intended to present a visual representation of the orientation of the weapon and its sights.



Front Sight Removal

Clamp the slide in a vice or any suitable holding fixture. Using a hammer and drift punch, or other suitable tool, push the roll pin out of the front sight and lift the sight off the post. Save the pin for assembly of the new front sight.

ML-10997 Sight - Installation

CAUTION: This sight contains a small glass ampule (the tritium light insert), and should not be subjected to severe direct impact. Use of a drift punch or other improper tools that damage the sights will void the warranty.

Front Sight Installation

Be sure that the embedded tritium light is facing the shooter, and push the ML-10997 sight down over the post, aligning the hole with the one in the post.

Once again, clamp the slide in a vice or any suitable holding fixture. Drift the roll pin back into the post.

MEPROLIGHT® SIGHTS

Made in Israel

Manufactured by: MEPROLIGHT

An ISO 9001 Quality Company ISO14001 environment OHSAS 18001 safety For inquiries, please contact:

USA

e-mail: sales@meprolight.us e-mail: support@meprolight.us www.meprolight.us

International (Except The USA) e-mail: sales@meprolight.com e-mail: support@meprolight.com www.meprolight.com

REV E